

PRODUCT DIMENSION (MM): H x W x D
99 x 247 x 373

WEIGHT (KG)
5.266

VOLTAGE
12V DC Input 230V AC Output

WATTAGE
1000W

CONTINUOUS POWER RATING (UP TO 12 HOURS)
1000W

PEAK POWER RATING (UP TO 200MS)
2000W

OUTPUT VOLTAGE
ADJUSTABLE: 200/220/230/240 +/- 10%

OUTPUT FREQUENCY
ADJUSTABLE: 50/60HZ

OUTPUT WAVEFORM
PURE SINE WAVE

INPUT VOLTAGE RANGE
9.5V - 16.5V (12V NOMINAL)

INPUT CURRENT
59A

EFFICIENCY AT 75% LOAD
90%

NO LOAD CURRENT DRAW
<1.5A

LOW BATTERY ALARM SOUNDS
10-11.5V +/- 0.5V

LOW BATTERY SHUT DOWN
9.5-11V +/- 0.5V

THERMAL PROTECTION
60° +/- 10°

USB
2.1A

DISPLAY PANEL PORT
YES

CURRENT SENSOR PORT
YES

E REGULATION
10 - EMC

POWER SAVING MODE
YES

POWER SAVING CURRENT
0.2A
